

## Intel PRO/Wireless 2915ABG

| Operating System   | General Features                                |                |                          |                             |                         |                 | Supported Authentication for Active associations |         |          |          |             |              |          |          |             |              |           |           |              |               |              |              |  |
|--|---|----------------|--------------------------|-----------------------------|-------------------------|-----------------|--|---------|----------|----------|-------------|--------------|----------|----------|-------------|--------------|-----------|-----------|--------------|---------------|--------------|--------------|--|
|  | Supported version (Previous versions or v 8.0?) | Packet Capture | 802.11n Capture (40 MHz) | 31 Channel scanning - 5 GHz | Extended Channel- 5 GHz | Noise detection | Open   | WEP-128 | LEAP-WEP | PEAP-WEP | EAP-TLS-WEP | EAP-FAST-WEP | LEAP-WPA | PEAP-WPA | EAP-TLS-WPA | EAP-FAST-WPA | LEAP-WPA2 | PEAP-WPA2 | EAP-TLS-WPA2 | EAP-FAST-WPA2 | WPA-PSK-TKIP | WPA2-PSK-AES |  |
| Operating System   |   |                |                          |                             |                         |                 |  |         |          |          |             |              |          |          |             |              |           |           |              |               |              |              |  |
| Windows XP with client utility                           | Client utility not supported                    |                |                          |                             |                         |                 |  |         |          |          |             |              |          |          |             |              |           |           |              |               |              |              |  |
| Windows XP with Windows Zero config (WLAN API Patch/SP3) | Previously supported                            | Supp           | NS                       | PS                          | NS                      | Supp            | Supp   | Supp    | NS       | NS       | NS          | NS           | NS       | NS       | NS          | NS           | NS        | NS        | NS           | NS            | NS           | NS           |  |
| Windows Vista  | Adapter not supported on Windows Vista          |                |                          |                             |                         |                 |  |         |          |          |             |              |          |          |             |              |           |           |              |               |              |              |  |

**NS: Not supported    Supp: Supported    Future:Future    NA: Not Applicable    PS: Partial Support**

Windows XP SP2 users: Download XP WLAN API Patch from : <http://www.microsoft.com/downloads/details.aspx?FamilyId=52A43BAB-DC4E-413F-AC71-158EFD1ADA50&displaylang=en>

Windows XP SP3 users: Do not install the Wireless LAN API Patch

### Notes for Windows XP with Windows Zero Config:

WEP-128 and LEAP-WEP do not need to be configured in WZC.

PEAP-WEP,EAP-TLS-WEP Users must have a profile configured in WZC and select Authentication type Host Based EAP within AirMagnet

PEAP-WPA,EAP-TLS-WPA Users must have a profile configured in WZC and select Authentication type Host Based EAP and check WPA within AirMagnet